

ERA 600 Performance

550W LED BASED PROFILE WITH FRAMING AND CMY COLOR MIXING

SPEC SHEET



Designed to fulfill the demand for a bright, compact, tour-worthy moving head, the Martin ERA 600 Performance combines a feature-loaded and rugged, yet cost-efficient profile for entertainment and rental applications.

It features a highly efficient 550W white LED engine that produces a bright, sharp 6,500K image projection with a flat field. Additional key benefits include 1:8 zoom, electronic dimming and strobe, full CMY color mixing and separate color wheel, variable color temperature control, animation wheel, iris for beam adjustment and fixed and rotating gobo wheels, loaded with user-favorite gobos from the renowned Martin MAC range that include a wide variety of effects, especially when combined with the two included rotating prisms and heavy frost filter.

Perfect for larger stage and live productions, the Martin ERA 600 Performance is ideal for a long list of scenarios, requiring a bright, yet truly versatile LED profile that offers near limitless design and usage potential.

KEY MESSAGES

FULL FRAMING SYSTEM

The full curtain framing system allows each of the four framing blades to cross the entire beam independently for full blackout. In addition, the entire framing module can rotate 120 degrees, allowing for precise and accurate image projection for the desired stage area. When fully focused, gobos can be framed with a soft edge, enabling designers a high degree of flexibility in the lighting design.

550 WATT LED LIGHT SOURCE

With an efficient 550 watt light source, the ERA 600 Performance delivers more output than similar-sized fixtures. Fully electronic dimming ensures extremely fast strobing, instant intensity control, and a flat, consistent field that can be maintained down to zero percent.

GREAT COLOR PALETTE

Precise color temperature control with variable color temperature correction (CTO). Vibrant CMY color mixing from light and smooth pastels to rich, saturated primaries. The color wheel produces nice color splits, fast color bumps & extends overall color gamut and brightness.

1:8 ZOOM RANGE

With 6 to 45 degrees of zoom, the ERA 600 Performance works great even on larger trim heights. Zooming is fast and accurate and maintains a high output throughout the range.

COMPACT AND DESIGNED FOR THE ROAD

The ERA 600 Performance is a very compact and low weight for its class making it easy to handle and rig. The modular design makes accessing & replacing of effects safe, quick, and easy – modules can be swapped in less than a minute.

ERA 600 Performance

550W LED BASED PROFILE WITH FRAMING AND CMY COLOR MIXING

SPEC SHEET

FEATURES

- Bright 550 watt / 6,500K LED light source
- 19,000 lumen output
- Crisp optics with flat field
- Fat beam look with 120 mm front lens
- 1:8 Fast zoom
- CMY color mixing – Vibrant color mixing with a superior palette of colors
- Linear CTO – Daylight to tungsten CCT control and expansion of the CMY palette
- 7-slot color wheel – for added color choice and split color effects
- Full Curtain Framing blades with +/- 60° rotation of entire system for flexible shape generation
- 7 rotating/indexing gobos – All renowned Martin glass gobos
- 8 static gobos for great morphing effects
- Animation wheel with continuous bi-directional rotation
- Two prisms – 4-facet and linear – rotation and index control for dynamic effects
- Heavy Frost – For wash effects
- Compact and low weight design

ORDERING INFORMATION

- Martin ERA 600 Performance in cardboard box.... P/N 9025122049
- Martin ERA 600 Performance – White in cardboard box..... P/N 9025122050
- Flightcase, two unit for ERA 600 P/N 91512205

INCLUDED ITEMS

- 2 x Omega brackets for rigging clamp attachment, TÜV approved

RELATED ITEMS

- Martin™ RDM 5.5 Splitter P/N 90758150
- Martin Companion Cable..... P/N 91616091
- Martin Companion Software Suite (including firmware uploader)



ERA 600 Performance

550W LED BASED PROFILE WITH FRAMING AND CMY COLOR MIXING

SPEC SHEET

ACCESSORIES

CABLES, 16 A, FOR CONNECTION TO POWER IN CHAINS

- Power input cable, H07RN-F, 2.5 mm², 14 AWG, bare ends to Neutrik TRUE1 NAC3FX-W (female), 1.5 m (4.9 ft.) P/N 91611797
- Power input cable, H07RN-F, 2.5 mm², 14 AWG, bare ends to Neutrik TRUE1 NAC3FX-W (female), 5 m (16.4 ft.)..... P/N 91611786
- Power input cable, SJ00W, 12 AWG, bare ends to Neutrik TRUE1 NAC3FX-W (female), 1.5 m (4.9 ft.)..... P/N 91610173
- Power input cable, SJ00W, 12 AWG, bare ends to Neutrik TRUE1 NAC3FX-W (female), 5 m (16.4 ft.)..... P/N 91610174

CABLES, 16 A, FOR RELAYING POWER IN CHAINS

- Power relay cable, H07RN-F, 2.5 mm², TRUE1 to TRUE1, 0.45 m (1.5 ft.)..... P/N 91611784
- Power relay cable, H07RN-F, 2.5 mm², TRUE1 to TRUE1, 1.2 m (3.9 ft.)..... P/N 91611785
- Power relay cable, H07RN-F, 2.5 mm², TRUE1 to TRUE1, 2.5 m (8.2 ft.)..... P/N 91611786
- Power relay cable, SJ00W, 12 AWG, TRUE1 to TRUE1, 0.45 m (1.5 ft.)..... P/N 91610170
- Power relay cable, SJ00W, 12 AWG, TRUE1 to TRUE1, 1.2 m (3.9 ft.)..... P/N 91610171
- Power relay cable, SJ00W, 12 AWG, TRUE1 to TRUE1, 2.5 m (8.2 ft.)..... P/N 91610172

CONNECTORS

- Power connector, cable mount, Neutrik TRUE1 NAC3FX-W (female) P/N 91611789
- Power connector, cable mount, Neutrik TRUE1 NAC3MX-W (male)..... P/N 91611788

INSTALLATION HARDWARE

- G-clamp (suspension with fixture hanging vertically downwards only) P/N 91602003
- Quick Trigger Clamp (suspension with fixture hanging vertically downwards only)..... P/N 91602007
- Half-coupler Clamp P/N 91602005
- Safety Cable, SWL 60 kg, BGV C1 / DGUV 17, black P/N 91604006
- Safety Cable, SWL 60 kg, BGV C1 / DGUV 17, silver P/N 91604007



ERA 600 Performance

550W LED BASED PROFILE WITH FRAMING AND CMY COLOR MIXING

SPEC SHEET

TECHNICAL SPECIFICATIONS

DYNAMIC EFFECTS

Electronic 'shutter' effect.....	Strobe effect, pulse effects, instant open and blackout
Electronic dimming	0 - 100%, four dimming curve options
Color mixing	CMY, independently variable 0-100%
Color temperature control	Variable 6500 - 2700 K
Color wheel.....	7 color filters plus open
Rotating gobo wheel.....	7 gobos plus open, wheel rotation, gobo rotation, indexing and shake
Static gobo wheel	8 gobos plus open, wheel indexing, rotation and shake
Gobo animation.....	Animation wheel, indexing, continuous rotation with variable speed and direction
Iris.....	0-100%
Zoom	Motorized
Focus.....	Motorized
Framing.....	Rotatable framing module, +/-60°, with 4 individually controllable full framing blades with variable angle and position.
Prism.....	2 rotating/indexing prisms (4-facet circular prism and 6-facet linear)
Frost.....	Heavy frost effect
Pan	540°, coarse & fine control and speed
Tilt.....	260°, coarse & fine control and speed

CONTROL AND PROGRAMMING

Control options	DMX
16-bit control	Dimming, pan and tilt
Setting and addressing	Control panel with backlit LCD display
DMX channels	41
DMX compliance	USITT DMX512/1990
RDM compliance.....	ANSI/ESTA E1.20
Transceiver	Opto-isolated RS-485

OPTICS AND SOURCE

Front Lens Diameter	120 mm
Zoom range	6° - 45°
Light source	550W LED engine
Minimum LED lifetime	20000 hours (to >70% luminous output)*

*Manufacturer's figure obtained under manufacturer's test conditions

PHOTOMETRIC DATA

Light engine luminous output.....	37000 lumens
Fixture luminous output.....	19000 lumens
CRI (Color Rendering Index)	>70
CCT.....	6500 Kelvin (+/- 350K)
LED refresh rate.....	3600 Hz

CONSTRUCTION

Housing	High-impact flame-retardant thermoplastic
---------------	---

Color.....	Black
Protection rating.....	IP 20

GOBOS

Gobo diameter	23.0 mm +0/- 0.2 mm (0.91 in. +/- 0.008 in.)
Maximum image diameter	19.0 mm (0.75 in.)
Gobo thickness, maximum.....	1.1 mm (0.04 in.)

INSTALLATION

Installation mounting points.....	Two quarter-turn brackets for rigging clamps
Orientation.....	Any

CONNECTIONS

AC power input, thru	Neutrik powerCON TRUE1
DMX data in/out	5-pin locking XLR

ELECTRICAL

AC power.....	100-240V nominal, 50/60 Hz
Power supply unit	Auto-ranging electronic switch mode
Steady Power Consumption	85W, all effects static, zero light output
Half-cycle RMS inrush current	21.7 A (at 230 V, 50 Hz)

TYPICAL POWER AND CURRENT

120V, 60Hz	6.5A, 778W, PF 0.994
230V, 50Hz	3.15A, 760W, PF 0.967

Measurements made at nominal voltage with all LEDs at full intensity. Allow for a deviation of +/- 10%. PF = power factor.

THERMAL

Cooling	Forced air (temperature regulated, low noise)
Maximum ambient temperature (Ta max.).....	40° C
Minimum ambient temperature (Ta min)	0° C
Maximum surface temperature, steady state.....	75° C (167° F) at 40° C ambient
Total heat dissipation	2660 BTU/hr. (calculated, +/- 10%)

APPROVAL

EU safety	EN 60598-2-17 [EN 60598-1), EN 62471, EN 62493
EU EMC.....	EN 55015; EN 55032; EN 55035; EN 61000-3-2,-3; EN 61547
US safety	UL 1573
US EMC.....	FCC Part 15 Class B
Canadian safety	CSA C22.2 No. 166
Canadian EMC.....	ICES-003 Class B, ICES-005 Class B
Australia/NZ	RCM
Global CB Certification/IECEE	IEC 60598-2-17 [IEC 60598-1)



ERA 600 Performance

550W LED BASED PROFILE WITH FRAMING AND CMY COLOR MIXING

SPEC SHEET

DIMENSIONS

PHYSICAL

Length..... 416 mm (16.4in.)
Width..... 290 mm (11.4in.)
Height..... 734 mm (28.9in.)
Weight..... 30.0 kg (66.1lbs)

