

MAC Encore™ Series CLD and WRM Acoustic Test Report



©2017 HARMAN Professional Denmark ApS. Information subject to change without notice. HARMAN Professional and all affiliated companies disclaim liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document.

Martin®, HARMAN® and all other trademarks in this document pertaining to services or products by HARMAN Professional or its affiliates and subsidiaries are registered as the property of HARMAN Professional Denmark ApS.

HARMAN Professional Denmark ApS - Olof Palmes Allé 44 - 8200 Aarhus N - Denmark - www.martin.com

Title

MAC Encore Series Acoustic Test Report

Test conditions

Test carried out according to ISO 3744:2010(E)

Devices tested

Make: HARMAN Professional Denmark ApS
Model: MAC Encore Performance, MAC Encore Wash
Variations: CLD, WRM
Serial no: 14200000306
Software version: 1.0.0

Results

An image of the test setup can be found on page 4. Test results are listed in Table 1 and Table 2 on pages 5 and 6.

HARMAN Professional Denmark ApS, R&D QA are responsible for the test results given in this report.

Environment

Temperature: 25.2°C Ta
Humidity: 46.2 %RH
AC mains power: 230 V, 50 Hz
Warm-up time: Minimum 30 minutes at full intensity.
Fixture placement: Fixture was placed at least one meter from walls and ceiling, as described in the Standard ISO 3744:2010(E)

Remarks

Test results apply only to the tested specimen.

Rev: (last five)	Made by:	Description:	Approved by:	Date approved:
A	Dennis Svane	MAC Encore Performance Sound Measurement	Markus Klüsener	2017-09-21
B	Bjørn Hansen	MAC Encore Series Idle noise measurements added	Henrik Kristensen	

Setup

The product was placed indoors in a hemi-anechoic chamber at the test facility of DELTA in Aarhus, Denmark (see Figure 1). The ceiling and walls were all acoustically absorbent and the floor was reflective. The main dimensions of the room were 12 m x 8 m x 4.5 m (length x width x height).



Figure 1: Test setup

The product was allowed a minimum of 30 minutes of warm-up time before measurements were performed.

Measurement method

Measurements were carried out using a setup with 4 microphones. The microphones were in turn moved to the measurement positions described below.

Measurement setup:

- Hemispherical measurement model
- 10 microphone positions in total
- Measurement surface area: 22.7 m²

Instrumentation

Please refer to Page 7 for a full instrumentation list.

Results - Operation

The MAC Encore Series fixtures were measured in 5 different scenarios:

1. All effects static, Light source ON, 100% output white light - Regulated Fan Mode
2. All effects static, Light source ON, 100% output white light - Constant Fan Mode Full
3. All effects static, Light source ON, 100% output white light - Constant Fan Mode Medium
4. All effects static, Light source ON, 100% output white light - Constant Fan Mode Low
5. All effects static, Light source ON, 100% output white light - Constant Fan Mode Ultra-Low

Sound Pressure Levels are listed in Table 1 below. Results of Sound Power Level measurements are listed in Table 3 on Page 7.

Sound Pressure Levels - Operation					
Distance from fixture	Regulated Fan (Max Output) [dB(A)]	Constant Fan Full [dB(A)]	Constant Fan Mid [dB(A)]	Constant Fan Low [dB(A)]	Constant Fan Ultra-Low [dB(A)]
LpA at 0m	46.0	51.0	47.7	44.6	42.5
LpA at 1m	38.0	43.0	39.7	36.6	34.5
LpA at 4m	26.0	31.0	27.7	24.6	22.5
LpA at 7m	21.1	26.1	22.8	19.7	17.6

Sound Pressure Levels have been converted from Sound Power Levels using the formula: $LpA = (LwA - \text{reduction}_{\text{distance}})$

Reductions used: 8dB(A)@1m, 20dB(A)@4m, 24.9dB(A)@7m

Table 1: Sound Pressure Levels

Results - Idle

The MAC Encore Series fixtures were measured in 1 scenarios¹:

1. All effects static, Light source OFF, Head horizontal - Regulated Fan Mode

Sound Pressure Levels – Idle	
Distance from fixture	Regulated Fan [dB(A)]
LpA at 0m	25.4
LpA at 1m	38.4
LpA at 4m	5.4
LpA at 7m	0.5

The duration of the acoustic measurement for each position is 30 seconds.

Sound Pressure Levels have been converted from Sound Power Levels using the formula:

$$LpA = (LwA - \text{reduction}_{\text{distance}})$$

Reductions used: 8dB(A)@1m, 20dB(A)@4m, 24.9dB(A)@7m

Table 2: Sound Pressure Levels at idle

¹ The product was placed indoors in a hemi-anechoic chamber at the intern test facility of Harman Professional.

The measurement results corrected for background noise are listed in the table below for 1/1-octave band and A-weighted values. Results marked with an (*) do not meet the 6 dB criterion in clause 4.2.1.1 of ISO 3744:2010(E) for the difference between measured sound power level and background noise.

1/1 Octave bands and A-weighted sound power levels

Measured Sound Power Levels					
1/1 Octave band, Hz	Regulated Fan (Max Output) [Lw, dB re.1pW]	Constant Fan Full [Lw, dB re.1pW]	Constant Fan Mid [Lw, dB re.1pW]	Constant Fan Low [Lw, dB re.1pW]	Constant Fan Ultra-Low [Lw, dB re.1pW]
63 Hz	10.4*	13.1	13.1	10.4*	10.9*
125 Hz	21.4*	23.4	22.2*	21.3*	21.2*
250 Hz	35.7	41.4	38.6	35.3	34.3
500 Hz	40.9	46.4	43.1	40.3	37.9
1000 Hz	42.3	46.5	43.5	40.1	37.3
2000 Hz	37.3	42.9	38.8	35.5	33.8
4000 Hz	28.8*	33.5	29.7*	28.0*	28.0*
8000 Hz	27.0*	28.7	27.3*	26.6*	26.4*
A-weighted (LwA, dB re.1pW)	46.0	51.0	47.7	44.6	42.5

These results are corrected for background noise with a maximum of 1.3 dB only.

Results marked with a () do not meet the 6 dB criterion in clause 4.2.1.1 in ISO 3744:2010(E) for the difference between measured sound pressure level and background noise.*

Table 3: Measured Sound Power Levels

Instrumentation

No.	Equipment	Make	Type
02L021	Calibrator	Brüel & Kjær	4231
14L002	Data acquisition card	National Instruments	NI9233
14L004	Data acquisition card	National Instruments	NI9233
06L038	½" Microphone	G.R.A.S	40AE
06L060	½" Microphone	G.R.A.S	40AE
06L063	½" Microphone	G.R.A.S	40AE
06L064	½" Microphone	G.R.A.S	40AE
09L032	Preamplifier	G.R.A.S	26CF
09L037	Preamplifier	G.R.A.S	26CF
09L044	Preamplifier	G.R.A.S	26CF
09L045	Preamplifier	G.R.A.S	26CF

Table 3: Instruments Used

The programs *noiseLAB Capture Professional version 4.0.4* and *Batch processor version 4.1* were used for recording and analysis. All instruments and programs are calibrated regularly in accordance with DANAK guidelines.

