

Specifications - Exterior

200

Physical

Length: 301 mm (11.9 in) / 431 mm (17.0 in)
Width: 310 mm (12.2 in)
Height: 402 mm (15.8 in)
Weight: 15 kg (33 lbs) / 16.6 kg (36.5 lbs)

Source

Lamp: 150W HIT
Approved models: Philips CDM-SA/T, GE CMH 150, Osram HQI-R, Osram HSD150/70
Base: GY 12

Control & Programming

Control options: DMX-512, stand-alone, host/client, Martin MC-X remote control
Receiver: RS-485
Setting and addressing: MP-2, DAD, MUM
Firmware update: Serial upload (MUF)
Stand-alone trigger options: Internal real-time clock with timer and light-level sensor
Stand-alone memory: 20 scenes
Data input/output: 1.8 m (5.9 ft) trailing cable w/ 3-pin XLR male & 3-pin XLR female
Data pin out Pin 1 shield, pin 2 cold (-), pin 3 hot (+)
DMX channels: 7

Dynamic effects

Cyan filter 0 - 100%
Magenta filter 0 - 100%
Yellow filter 0 - 100%
Dimmer 0 - 100%

Installation

Minimum distance to combustible materials: 1 m (39 in)
Minimum distance to illuminated surfaces: 0.5 m (20 in)

Thermal

Maximum ambient temperature: (T_a) 40° C (104° F)
Maximum surface temperature, steady state, $T_a = 40^\circ$ 90° C (194° F)
Cooling Convection

Maximum heat output

195 V @ 50/60 Hz665 BTU/hour
210 V @ 50/60 Hz716 BTU/hour
225 V @ 50/60 Hz767 BTU/hour
245 V @ 50/60 Hz836 BTU/hour
277 V @ 50/60 Hz945 BTU/hour

* These measurements have a margin of error of +/- 10%

AC Supply

AC input: 1.8 m (5.9 ft) trailing cable w/o cord cap
Power supply options: 195/210/225/245/277 V, 50/60 Hz
Primary fuse T 3.15 A, high I^2t , 250 V
Fuse F1 T 2A, 250 V
Fuse F2 T 2A, 250 V

Maximum power and current

195 V @ 50/60 Hz210 W, 1.2 A
210 V @ 50/60 Hz220 W, 1.1 A
225 V @ 50/60 Hz200 W, 1.0 A
245 V @ 50/60 Hz200 W, 0.9 A
277 V @ 50/60 Hz200 W, 0.8 A

* These measurements have a margin of error of +/- 10%

Construction

Housing: extruded aluminum
Finish: anodized, natural aluminum color
Front glass: 6 mm (0.24 in) anti-reflection coated
Mounting bracket: 8 mm (0.3 in) anodized aluminum
Housing-to-bracket attachment:4 stainless steel M6 bolts, A2 DIN 933, 18.8
Protection factor: IP 65

Listings

ETL, ETL, CE

Photometrics - Exterior 200

Efficiency	39%
Half peak angle.....	38°
One-tenth-peak angle	60°
Illuminance.....	12263/distance ² lux
Half-peak diameter	0.64 x distance m
One-tenth-peak diameter	0.99 x distance m
Measurement conditions	230V, 50Hz, no color applied
Measurement source.....	Philips CDM-SA/T 150W

Photometrics - Exterior 200 with beam-shaper lens

Efficiency	31%
Half peak angle.....	41° / 46° 0/90 degrees
One-tenth-peak angle	83° / 91° 0/90 degrees
Illuminance.....	5647/distance ² lux
Half-peak diameter	0.75 x distance m
One-tenth-peak diameter	1.38 x distance m
Measurement conditions	230V, 50Hz, no color applied
Measurement source.....	Philips CDM-SA/T 150W

Photometrics - Exterior 200 with Fresnel lens

Efficiency	38%
Half peak angle.....	21°
One-tenth-peak angle	34°
Illuminance.....	37721/distance ² lux
Half-peak diameter	0.35 x distance m
One-tenth-peak diameter	0.58 x distance m
Measurement conditions	230V, 50Hz, no color applied
Measurement source.....	Philips CDM-SA/T 150W

Photometrics - Exterior 200 with micro-diffuser lens

Efficiency	40%
Half peak angle.....	42°
One-tenth-peak angle	71°
Illuminance.....	10076/distance ² lux
Half-peak diameter	0.72 x distance m
One-tenth-peak diameter	1.17 x distance m
Measurement conditions	230V, 50Hz, no color applied
Measurement source.....	Philips CDM-SA/T 150W

Included items

User manual

Lamp: Philips CDM-SA/T 150 W

Accessories

Fresnel lens	P/N 91610022
Micro diffuser lens.....	P/N 91610024
Beam shaper lens	P/N 91610023
MC-X Controller, 220 - 245 V, 50 Hz	P/N 90718200
MC-X Controller, 110 - 120 V, 60 Hz	P/N 90718300
Philips CDM-SA/T 150 W lamp	P/N 97010111
Snoot/barndoor kit	P/N 91611031
Extensions to Snoot/barndoor kit	P/N 91611032
DAD, DMX Address Device	P/N 90758430
MUM, Multi Utility Manager	P/N 90758090
MP-2 Uploader	P/N 90758420

Ordering information

Exterior 200, 60°, 230V, 50Hz	P/N 90509000
Exterior 200, 60°, 245V, 50Hz	P/N 90509002
Exterior 200, 60°, 210V, 60Hz	P/N 90509004
Exterior 200 Long Barrel, 12°, 230V, 50Hz	P/N 90509020
Exterior 200 Long Barrel, 12°, 245V, 50Hz	P/N 90509022
Exterior 200 Long Barrel, 12°, 210V, 60Hz	P/N 90509024
Exterior 200 Long Barrel, 22°, 230V, 50Hz	P/N 90509040
Exterior 200 Long Barrel, 22°, 245V, 50Hz	P/N 90509042
Exterior 200 Long Barrel, 22°, 210V, 60Hz	P/N 90509044