

# SPECIFICATIONS – WDMX-512

## Standard model

Mains inlet.....	230 V AC/115 V AC (IEC Connector) $\pm 7\%$ ,
Power consumption.....	10 W
Protocol.....	DMX512
Communication distance.....	up to 200 m (666 ft), outdoor, without repeater
DMX Refresh rate.....	Approx 44 Hz
DMX I/O.....	5 pin XLR
Expandability.....	up to 13 DMX-512 universes
WLAN Card.....	802.11B, PCMCIA, Prism-II Chipset or compatible
Size (h, w, d).....	50 x 195 x 125 mm (1.96 x 7.68 x 4.9 inch)
Weight.....	1.5 kg (53 oz.)
Temperature operating range.....	0°-40° C (32°-104° F)

## ProDiversity model

Mains inlet.....	230 V AC/115 V AC (IEC Connector) $\pm 7\%$
Power consumption.....	10 W
Protocol.....	DMX512
Communication distance.....	up to 300 m (1.000 ft), outdoor, without repeater
DMX Refresh rate.....	Approx 44 Hz
DMX I/O.....	5 pin XLR
Expandability.....	up to 13 DMX-512 universes
WLAN Card.....	802.11B, PCMCIA, Prism-II Chipset or compatible
Size (h, w, d).....	44 x 482 x 182 mm (1.73 x 19.00 x 7.17 inch)
Weight.....	3.5 kg (124 oz.)
Temperature operating range.....	0°-40° C (32°-104° F)