

SPECIFICATIONS - CYCLO DMX

PHYSICAL - CYCLO 04 DMX

L x W x H	1190 x 99 x 91 mm (50 x 3.9 x 3.6 in.)
Weight	6.7 kg (14.8 lbs)
Fixture color	Grey

PHYSICAL - CYCLO 03 DMX

L x W x H	1190 x 81 x 91 mm (50 x 3.2 x 3.6 in.)
Weight	6.5 kg (14.3 lbs)
Fixture color	Grey

INSTALLATION

Orientation	any
Minimum free space around fixture when installed	25 mm (1 inch)

SOURCE

Approved lamp type	OSRAM T5 FH 28 watt tubes
Light source	T5 tubes (28W)
Expected lamp life	20000 hours

POWER

AC power	198 V - 254 V, 50 / 60 Hz
Maximum power and current @ 230 V / 50 Hz	0.56 A / 128 watts
AC input	EnstoNet Installation System connector/plug (not supplied)

THERMAL

Maximum ambient temperature (T _a)	40° C (104° F)
Cooling	convection

DYNAMIC EFFECTS

Dimmable tubes	Red, green, blue and white (Cyclo 04 DMX only)
Independent dimming of each tube via DMX control device	

CONTROL AND PROGRAMMING

Control options	DMX512, stand alone, master/slave
Receiver	RS-485
Setting and addressing	DIP switch
Data input	RJ-45
Data output	RJ-45
DMX channels (Cyclo 03 DMX)	3
DMX channels (Cyclo 04 DMX)	4

ORDERING INFORMATION

Cyclo 04 DMX	P/N 90550005
Cyclo 03 DMX	P/N 90550015

INCLUDED ITEMS

LampOSRAM T5 FH28W/60 (red)
LampOSRAM T5 FH 28W/66 (green)
LampOSRAM T5 FH28W/67 (blue)
LampOSRAM T5 FH28W/840 (white) - (Cyclo 04 DMX only)
User manual

ACCESSORIES

Diffuser front for Cyclo 04P/N 91611078
Diffuser front for Cyclo 03P/N 91611077
Termination Plug RJ-45P/N 91613028
ENSTO 3 pole 16A/250V male connectorP/N 05347202
ENSTO 3 pole 16A/250V female connectorP/N 05327202
RJ-45 connector (15 cm/ 5.9 in.)P/N 11840088
ENSTO Male/female cable (15 cm/5.9in.)P/N 11501019
XLR male to RJ-45 converterP/N 11840087
XLR female to RJ-45 connectorP/N 11840086
CAT5 network cables - 2 m (6.5 ft) x 50 piecesP/N 91611044
CAT5 network cables - 5 m (16.4 ft) x 30 piecesP/N 91611045
CAT5 network cables - 10 m (32.8 ft) x 15 piecesP/N 91611045