

Mounting: Standing or optional hanging
Orientation: Up to +/- 30° from horizontal
Clearance around machine: 100 mm (4 in.)

Connections

AC Power: Neutrik PowerCon
DMX, link mode in/out: 5-pin locking XL
Remote control: 3-pin locking XLR
Firmware: AVR socket

Electrical

EU model

AC power : 220-240 V, 50/60 Hz
Main fuse: 6.3 AT (slow blow) 250 V
Typical power and current: 1010 W, 4.4 A*

US model

AC power: 110-120 V, 50/60 Hz
Main fuse: 10 AT (slow blow) 125 V
Typical power and current: 1042 W, 8.68 A*

*Measurements made at nominal voltage. Allow for a deviation of +/- 10%:

Thermal

Maximum ambient temperature (Ta max.): 40° C (104° F)
Minimum ambient temperature (Ta min): 5° C (41° F)
Exterior surface temperature, steady state: 30° C (86° F)
Maximum nozzle temperature: 290° C (554° F)

Approvals

EU model

8QLWHG.LQJGRP8.&\$
(U safety: EN 60335-1+A15, EN 62233
EU EMC: EN 61000-6-3
EU Immunity: EN 61000-6-1
Australia/NZ (pending): RCM

US model

Calibration factors have been developed and approved by the Actors' Equity Association and the Broadway League for use in measuring theatrical haze with the JEM™ Compact Hazer Pro and JEM™ C-Plus Haze Fluid

Included Items

Fluid reservoir, 2.5 l: P/N 34300521
Power input cable, EU, powerCON, stripped ends, 2.5 m (8.2 ft): P/N 11501041
Power input cable, US, powerCON, molded NEMA 5-15P, 2.5 m (8.2 ft): P/N 11501042

Accessories

JEM™ Compact Hazer Pro Air Director: P/N 92625011
JEM™ Compact Hazer Pro Digital Remote Control: P/N 92765040
JEM Compact Hazer Pro™ Flying Kit: P/N 92610003
-(O([WHUQDO)OXLG5HVHUYRLU.LW O31

Approved fluids

JEM™ C-Plus Haze Fluid
JEM™ Pro Clean Supreme

*Various sizes available - contact your dealer or see 'Fluids' product pages for details

Installation Accessories

G-clamp: P/N 91602003
Half-coupler clamp: P/N 91602005
Quick trigger clamp: P/N 91602007
Safety cable, SWL 60 kg, BGV C1/ DGUV 17, black: P/N 91604006
Safety cable, SWL 60 kg, BGV C1/ DGUV 17, silver: P/N 91604007

Service Tools

Epsilon 5 AVR Programmer: P/N 50502004
Temperature Calibration Box: P/N 92620005

Ordering Information

JEM™ Compact Hazer Pro, EU: P/N 92225950
JEM™ Compact Hazer Pro, US: P/N 92225960

