

SPECIFICATIONS - CYCLO 04 DMX WALLWASHER

PHYSICAL

L x W x H 1210 x 290 x 94 mm (47.6 x 11.4 x 3.7 in.)
Weight 9 kg (20 lbs)

INSTALLATION

Installation space (L x W) 1200 x 275 mm +/-15 mm (47 x 11 in. +/-0.5 in.)
Installation space depth 120 mm (4.7 in.)
Minimum free space around fixture when installed 25 mm (1 inch)

SOURCE

Approved lamp type OSRAM T5 FH 28 watt tubes
Light source T5 tubes (3x28W)

POWER

AC power 198 V - 254 V, 50 / 60 Hz
Dimmer control 1-10V control
Maximum power and current @ 230 V / 50 Hz 0.56 A / 128 watts

THERMAL

Maximum ambient temperature (Ta) 40° C (104° F)

DYNAMIC EFFECTS

Dimmable tubes Red, green, blue and white
Independent dimming of each tube via DMX control device

CONTROL AND PROGRAMMING

Control options DMX512, stand alone, master/slave
Receiver RS-485
Setting and addressing DIP switch
Data input RJ-45
Data output RJ-45
DMX channels 4

ORDERING INFORMATION

Cyclo 04 DMX Wallwasher P/N 90550035

INCLUDED ITEMS

Lamp OSRAM T5 FH28W/60 (red)
Lamp OSRAM T5 FH 28W/66 (green)
Lamp OSRAM T5 FH28W/67 (blue)
Lamp OSRAM T5 FH28W/840 (white)
User manual

ACCESSORIES

Termination Plug RJ-45	P/N 91613028
XLR male to RJ-45 converter	P/N 11840087
XLR female to RJ-45 connector	P/N 11840086
CAT5 network cables - 2 m (6.5 ft) x 50 pieces	P/N 91611044
CAT5 network cables - 5 m (16.4 ft) x 30 pieces	P/N 91611045
CAT5 network cables - 10 m (32.8 ft) x 15 pieces	P/N 91611045
CAT5 network cable - 0.25 m (10 in.) x 1 piece	P/N 11840088
ENSTO 3 pole 16A/250V male connector	P/N 05347202
ENSTO 3 pole 16A/250V female connector	P/N 05327202
ENSTO male/female cable (15 cm/5.9in.)	P/N 11501019