

# M14T Specifications

## Passive mode:

Power rating IEC 268:	450 watt
Power rating Peak:	1680 watt
Sensitivity:	102dB
Max SPL, calculated long term:	129 dB
Max SPL, Peak	135 dB
Frequency range +- 3dB:	65Hz – 20 KHz
LF	15"
HF	2"
Dispersion	55 x 45
Flying system	Flying tracks accept double stud
Recommended amplifier:	650 watt

## Drive units:

<u>Woofers:</u>	15" with 3" voice coil
Nominal impedance:	8 ohm
Power handling AES:	400 watt
Sensitivity 1W/1m	102 dB
Max SPL, calculated long term:	129 dB
Max SPL, Peak	135 dB
Recommended amplifier:	650 watt

<u>Compression driver:</u>	3" diaphragm, 2" throat
Nominal impedance	16 ohm
Power handling AES:	150 watt
Sensitivity 1W/1m	110dB
Max SPL, calculated long term:	132 dB
Max SPL, Peak	138 dB
Recommended amplifier:	200 watt

## Weight & Measurements

Dimension	67 x 45 x 40 cm (26 x 18 x 16 in.)
Weight	32 kg (71 lbs)

Finish:	Black safeCoat coating
Input connector:	2 x Speakon NL 4 with link
Top-hat adaptor:	35 mm ( 1.4 in.)