

SPECIFICATIONS - MANIA DC2

PHYSICAL

Size without mounting bracket (LxWxH) . . . 312 x 250 x 142mm (12.3 x 9.8 x 14.2in)
Weight 6.3 kg (14lb)

CONSTRUCTION

Housing steel and aluminum

THERMAL

Exterior surface temperature under steady state condition 60°C (140°F)
Time required to cool before handling at least 5 minutes
Maximum ambient temperature (T_a) 40° C (104°F)

INSTALLATION

Minimum distance to flammable material 0.3 m (1ft)
Minimum distance to illuminated surface 1.0 m (3.3ft)
Minimum clearance around air vents 0.1 m (4in)

ELECTRICAL

Input 3-prong IEC male socket
AC Power . . . switch selectable, operating ranges 115-120 V / 220-240 V, 50-60 Hz
Main fuse 2 AT (time delay),

TYPICAL POWER AND CURRENT

120 V, 50 Hz 118 W, 1 A
120 V, 60 Hz 117 W, 1 A
230 V, 50 Hz 109 W, 0.5 A
230 V, 60 Hz 109 W, 0.5 A
240 V, 50 Hz 117 W, 0.5 A
240 V, 60 Hz 117 W, 0.5 A

CONTROL AND PROGRAMMING

Effect rotation direction
Effect rotation speed

PHOTOMETRICS

Beam angle 53°

INCLUDED ITEMS - US VERSION

2 m (6.5 ft) US mains cable 18AWG with US male connector (UL approved)
Philips 12V EFP/8H 100W lamp
User manual

INCLUDED ITEMS - NON-US VERSION

3 m (9.8 ft) EU mains cable 3x1.0mm² with Schuko male connector
3 m (9.8 ft) EU mains cable 3x1.0mm² with no male connector
Philips 12V EFP/8H 100W lamp
User manual

ACCESSORIES

Philips 12V EFP/8H 100W lamp P/N 97000004
Half-coupler clamp P/N 91602005
Fuse (2 AT) P/N 05020009

ORDERING INFORMATION

Mania DC2 US version P/N 90430021
Mania DC2 non-US version P/N 90430020