

# M•FLEX SUB SPECIFICATIONS

---

## SYSTEM PERFORMANCE

Max long term SPL (calculated) . . . . .	123 dB
Max peak SPL (calculated) . . . . .	129 dB
Frequency range +/- 10dB . . . . .	45 - 250 Hz
Auto stand-by . . . . .	1 hour

## TRANSDUCER

Type . . . . .	15" coaxial with 3" voice coil
Power rating, IEC 268 . . . . .	320 W
Power rating, peak . . . . .	1280 W
Sensitivity . . . . .	97 dB

## AMPLIFIER

LF output, continuous RMS . . . . .	350 W
High pass filter . . . . .	115 Hz, 24 dB LR

## LINE INPUT

Type . . . . .	Balanced
Impedance . . . . .	22 K ohm

## ELECTRICAL

AC input, US model . . . . .	110 V, 60 Hz
AC input, EU model . . . . .	230 V, 50 Hz
Power consumption, peak . . . . .	510 W
Power consumption, average . . . . .	185 W
Power consumption, no signal . . . . .	53 W
Power consumption, standby . . . . .	5 W
Maximum current consumption . . . . .	2.23 A @ 230 V, 4.46 A @ 115 V

## PHYSICAL

Dimensions . . . . .	67 x 48 x 40 cm (26 x 19 x 16 in.)
----------------------	------------------------------------

## ACCESSORIES

- Speaker cover
- Flying bracket for cluster and array configuration